



ELEVATORI IDRAULICI DUPLEX

Duplex hydraulic forklifts

CM 16DBCH



**Elevatore per trattori di media potenza.
Robusto e bilanciato. Offre all'operatore la massima visibilità.**

- Cuscinetti radiali a rulli cilindrici
- Due catene di sollevamento standard
- Profili in acciaio ad "H" laminati a caldo
- Due cilindri laterali di sollevamento a doppio effetto
- Attacco a 3 punti cat. 2
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

***Hydraulic forklift suitable to medium power tractors.
Sturdy and balanced. Provide the operator with great visibility.***


- *Cylindrical roller bearings*
- *Two standard lifting chains*
- *"H" shaped hot rolled steel profiles*
- *Two lateral double effect lifting cylinders*
- *Cat.2 three point linkage*
- *Distributor with 4 levers*
- *Side shift sliding on self lubricating bushes*
- *Adjustable and pliable forks*
- *Tilting cylinder with adjustable junction*
- *Connecting hoses to the tractor*



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings



Catene di sollevamento standard
Standard lifting chains



Distributore 4 leve
Distributor with 4 levers



Forche pieghevoli e regolabili
Adjustable and pliable forks



Traslatore laterale
Side shift



Ottima visibilità
Great visibility



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM 16DBCH				
MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
16 DBCH 2200	1600	2200	1800	400
16 DBCH 2800	1600	2800	2100	440
16 DBCH 3200	1600	3200	2300	475
16 DBCH 3600	1600	3600	2500	500
16 DBCH 4000	1600	4000	2700	500