



## ELEVATORI IDRAULICI DUPLEX

*Duplex hydraulic forklifts*

### CM 16DC



**Elevatore idraulico duplex per trattori di media potenza.  
Il più leggero ed economico della sua gamma.**


- Cuscinetti radiali a rulli cilindrici
- Catena di sollevamento "Fleyer"
- Profili in acciaio ad "U" laminato a caldo
- Cilindro di sollevamento a doppio effetto
- Attacco a 3 punti cat. 2
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

***Duplex hydraulic forklift suitable to medium power tractors.  
The lighter and cheaper of its range.***

- Cylindrical roller bearings
- "Fleyer" lifting chain
- "U" shaped hot rolled steel profiles
- Double effect lifting cylinder
- Cat.2 three point linkage
- Distributor with 4 levers
- Side shift sliding on self lubricating bushes
- Adjustable and pliable forks
- Tilting cylinder with adjustable junction
- Connecting hoses to the tractor



**Cuscinetti radiali a rulli cilindrici**  
*Straight roller radial bearings*



**Catena di sollevamento tipo "Fleyer"**  
*"Fleyer" type lifting chain*



**Distributore 4 leve**  
*Distributor with 4 levers*



**Forche pieghevoli e regolabili**  
*Adjustable and pliable forks*



**Traslatore laterale**  
*Side shift*



**Profili in acciaio laminati a caldo**  
*Hot-rolled steel profiles*

CM 16DC				
MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
<b>16 DC 1600</b>	1600	1600	1580	328
<b>16 DC 2000</b>	1600	2000	1780	344
<b>16 DC 2500</b>	1600	2500	2050	370
<b>16 DC 3000</b>	1600	3000	2300	384
<b>16 DC 3200</b>	1600	3200	2400	392
<b>16 DC 3600</b>	1600	3600	2600	410
<b>16 DC 4000</b>	1600	4000	2800	430