



ELEVATORI IDRAULICI TRIPLEX

Triples hydraulic forklifts

CM 16TBCH



Elevatore per trattore di media potenza. Dotato di eccezionale visibilità.


- Cuscinetti radiali a rulli cilindrici
- Quattro catene di sollevamento "Fleyer"
- Profili in acciaio ad "U" ed "H" laminati a caldo
- Due cilindri laterali di sollevamento a doppio effetto
- Attacco a tre punti cat. 2
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

Hydraulic forklift suitable to medium power tractor. Provide the operator with great visibility.


- *Cylindrical roller bearings*
- *Four "Fleyer" lifting chains*
- *"U" and "H" shaped hot rolled steel profiles*
- *Two lateral double effect lifting cylinders*
- *Cat.2 three point linkage*
- *Distributor with 4 levers*
- *Side shift sliding on self lubricating bushes*
- *Adjustable and pliable forks*
- *Tilting cylinder with adjustable junction*
- *Connecting hoses to the tractor*



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings



Catene di sollevamento tipo "Fleyer"
"Fleyer" type lifting chains



Distributore 4 leve
Distributor with 4 levers



Forche pieghevoli e regolabili
Adjustable and pliable forks



Traslatore laterale
Side shift



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM 16TBCH

MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
16 TBCH 2500	1600	2500	1560	438
16 TBCH 3000	1600	3000	1730	470
16 TBCH 3200	1600	3200	1790	480
16 TBCH 3600	1600	3600	1930	520
16 TBCH 4000	1600	4000	2130	550
16 TBCH 4500	1600	4500	2300	600
16 TBCH 5200	1600	5200	2530	680