



ELEVATORI IDRAULICI TRIPLEX

Triplex hydraulic forklifts

CM 16TC



**Elevatore idraulico per trattore di media potenza.
Leggero può ottenere la massima altezza con il minimo ingombro.**


- Cuscinetti radiali a rulli cilindrici
- Catena di sollevamento "Fleyer"
- Profili in acciaio ad "U" laminati a caldo
- Cilindro di sollevamento a doppio sfilo
- Attacco a tre punti cat. 2
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

*Hydraulic forklift suitable to medium power tractor.
Light, it allows to reach great heights
in the minimum space.*


- Cylindrical roller bearings
- "Fleyer" lifting chain
- "U" shaped hot rolled steel profiles
- Double extension lifting cylinder
- Cat.2 three point linkage
- Distributor with 4 levers
- Side shift sliding on self lubricating bushes
- Adjustable and pliable forks
- Tilting cylinder with adjustable junction
- Connecting hoses to the tractor



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings



Catena di sollevamento tipo "Fleyer"
"Fleyer" type lifting chain



Distributore 4 leve
Distributor with 4 levers



Forche pieghevoli e regolabili
Adjustable and pliable forks



Traslatore laterale
Side shift



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM 16TC				
MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
16 TC 2500	1600	2500	1480	350
16 TC 3000	1600	3000	1730	395
16 TC 3200	1600	3200	1790	410
16 TC 3600	1600	3600	1930	450