



ELEVATORI IDRAULICI TRIPLEX

Triplex hydraulic forklifts

CM 16THAL



Elevatore idraulico per trattori di media potenza.

Dotato di alzata libera che consente di sollevare il carico senza variare l'ingombro.

- Cuscinetti radiali a rulli cilindrici
- Due catene di sollevamento "Fleyer"
- Profili in acciaio ad "U" ed "H" laminati a caldo
- Cilindro di sollevamento a doppio sfilo
- Attacco a tre punti cat. 2
- Alzata libera 200 mm
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

***Hydraulic forklift suitable to medium power tractors.
Equipped with free lifting for raising the load without
changing overall dimensions.***

- *Cylindrical roller bearings*
- *Two "Fleyer" lifting chains*
- *"U" and "H" shaped hot rolled steel profiles*
- *Double extension lifting cylinder*
- *Cat.2 three point linkage*
- *Free lifting 200 mm*
- *Distributor with 4 levers*
- *Side shift sliding on self lubricating bushes*
- *Adjustable and pliable forks*
- *Tilting cylinder with adjustable junction*
- *Connecting hoses to the tractor*



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings



Catene di sollevamento tipo "Fleyer"
"Fleyer" type lifting chains




Distributore 4 leve
Distributor with 4 levers



Forche pieghevoli e regolabili
Adjustable and pliable forks



Traslatore laterale
Side shift



Alzata libera
Free lifting



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM 16THAL

MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
16 THAL 2500	1600	2500	1480	390
16 THAL 3000	1600	3000	1650	445
16 THAL 3200	1600	3200	1730	465
16 THAL 3600	1600	3600	1850	510